



**DISTANZIALE SAE
CON FORO
LATERALE**



**SAE DISTANCE
PIECE WITH
LATERAL HOLE**

| Pressione max di esercizio raccomandata Kg/cm ² | Grandezza | Tipo | Dimensioni | | | | | | | | Viti | | Or tipo | Peso Kg |
|--|-----------|------|------------|---|---|---|---|---|---|---|--------|-----|---------|-----------|
| | | | Dimensions | | | | | | | | Screws | | | |
| Maximum recommended working pressure Kg/cm ² | Size | Type | A | C | D | E | F | H | L | W | Metric | Unc | Or type | Weight Kg |

SERIE 3000

| | | | | | | | | | | | | | | |
|-----|-------|------------|------|--------|-----|-------|-----|----|------|----------------|--------|-------------|------|------|
| 345 | 3/4" | D100G1/8 | 19 | 47,63 | 71 | 22,23 | 60 | 19 | 11 | G1/8 - M10x1 | M10x55 | 3/8"x2"1/4 | 4100 | 0,42 |
| 345 | 3/4" | D100G1/4 * | 19 | 47,63 | 71 | 22,23 | 60 | 25 | 11 | G1/4 - M12x1,5 | M10x60 | 3/8"x2"1/2 | 4100 | 0,55 |
| 345 | 1" | D102G1/8 | 25,0 | 52,37 | 71 | 26,19 | 60 | 19 | 11 | G1/8 - M10x1 | M10x55 | 3/8"x2"1/4 | 4131 | 0,35 |
| 345 | 1" | D102G1/4 * | 25,0 | 52,37 | 71 | 26,19 | 60 | 26 | 11 | G1/4 - M12x1,5 | M10x60 | 3/8"x2"1/2 | 4131 | 0,53 |
| 276 | 1"1/4 | D104G1/8 | 32 | 58,72 | 81 | 30,18 | 68 | 22 | 11,5 | G1/8 - M10x1 | M10x60 | 7/16"x2"1/2 | 4150 | 0,45 |
| 276 | 1"1/4 | D104G1/4 | 32 | 58,72 | 81 | 30,18 | 70 | 22 | 11,5 | G1/4 - M12x1,5 | M10x60 | 7/16"x2"1/2 | 4150 | 0,59 |
| 207 | 1"1/2 | D106G1/8 | 38 | 69,85 | 95 | 35,71 | 78 | 25 | 13,5 | G1/8 - M10x1 | M12x70 | 1/2"x2"3/4 | 4187 | 0,88 |
| 207 | 1"1/2 | D106G1/4 | 38 | 69,85 | 95 | 35,71 | 78 | 25 | 13,5 | G1/4 - M12x1,5 | M12x70 | 1/2"x2"3/4 | 4187 | 0,88 |
| 207 | 2" | D108G1/8 | 51 | 77,77 | 102 | 42,88 | 90 | 18 | 13,5 | G1/8 - M10x1 | M12x65 | 1/2"x2"1/2 | 4225 | 0,78 |
| 207 | 2" | D108G1/4 | 51 | 77,77 | 112 | 42,88 | 94 | 24 | 13,5 | G1/4 - M12x1,5 | M12x70 | 1/2"x2"3/4 | 4225 | 1,16 |
| 172 | 2"1/2 | D110G1/8 | 63 | 88,90 | 114 | 50,80 | 105 | 18 | 13,5 | G1/8 - M10x1 | M12x65 | 1/2"x2"1/2 | 4275 | 0,90 |
| 172 | 2"1/2 | D110G1/4 | 63 | 88,90 | 114 | 50,80 | 105 | 25 | 13,5 | G1/4 - M12x1,5 | M12x70 | 1/2"x2"3/4 | 4275 | 1,26 |
| 138 | 3" | D112G1/8 | 73 | 106,38 | 134 | 61,93 | 124 | 23 | 17,5 | G1/8 - M10x1 | M16x75 | 5/8"x3" | 4337 | 1,63 |
| 138 | 3" | D112G1/4 | 73 | 106,38 | 134 | 61,93 | 124 | 23 | 17,5 | G1/4 - M12x1,5 | M16x75 | 5/8"x3" | 4337 | 1,63 |

SERIE 6000

| | | | | | | | | | | | | | | |
|-----|-------|--------------|----|-------|-----|-------|-----|----|------|----------------|---------|-------------|------|------|
| 414 | 1/2" | D401G1/8 | 13 | 40,49 | 56 | 18,24 | 48 | 16 | 9 | G1/8 - M10x1 | M8x45 | 5/16"x1"3/4 | 4075 | 0,22 |
| 414 | 1/2" | D401G1/4 * | 13 | 40,49 | 71 | 18,24 | 60 | 25 | 9 | G1/4 - M12x1,5 | M8x55 | 5/16"x2"1/4 | 4075 | 0,60 |
| 414 | 3/4" | D402G1/8 | 19 | 50,80 | 71 | 23,80 | 60 | 19 | 11 | G1/8 - M10x1 | M10x60 | 3/8"x2"1/2 | 4100 | 0,42 |
| 414 | 3/4" | D402G1/4 * | 19 | 50,80 | 71 | 23,80 | 60 | 25 | 11 | G1/4 - M12x1,5 | M10x65 | 3/8"x2"1/2 | 4100 | 0,55 |
| 414 | 1" | D403G1/8 | 25 | 57,15 | 81 | 27,76 | 70 | 22 | 13 | G1/8 - M10x1 | M12x65 | 7/16"x2"1/2 | 4131 | 0,63 |
| 414 | 1" | D403G1/4 | 25 | 57,15 | 81 | 27,76 | 70 | 22 | 13 | G1/4 - M12x1,5 | M12x65 | 7/16"x2"1/2 | 4131 | 0,62 |
| 414 | 1"1/4 | D404G1/8 | 32 | 66,68 | 95 | 31,75 | 78 | 25 | 15 | G1/8 - M10x1 | M14x70 | - | 4150 | 0,93 |
| 414 | 1"1/4 | D404G1/8 L13 | 32 | 66,68 | 95 | 31,75 | 78 | 25 | 13,5 | G1/8 - M10x1 | M12x70 | 1/2"x2"3/4 | 4150 | 0,93 |
| 414 | 1"1/4 | D404G1/4 | 32 | 66,68 | 95 | 31,75 | 78 | 25 | 15 | G1/4 - M12x1,5 | M14x70 | - | 4150 | 0,92 |
| 414 | 1"1/4 | D404G1/4 L13 | 32 | 66,68 | 95 | 31,75 | 78 | 25 | 13,5 | G1/4 - M12x1,5 | M12x70 | 1/2"x2"3/4 | 4150 | 0,92 |
| 414 | 1"1/2 | D405G1/8 | 38 | 79,38 | 112 | 36,50 | 94 | 28 | 17 | G1/8 - M10x1 | M16x85 | 5/8"x3"1/2 | 4187 | 1,50 |
| 414 | 1"1/2 | D405G1/4 | 38 | 79,38 | 112 | 36,50 | 94 | 28 | 17 | G1/4 - M12x1,5 | M16x85 | 5/8"x3"1/2 | 4187 | 1,48 |
| 414 | 2" | D406G1/8 | 51 | 96,82 | 134 | 44,45 | 114 | 28 | 21 | G1/8 - M10x1 | M20x100 | 3/4"x4" | 4225 | 2,05 |
| 414 | 2" | D406G1/4 | 51 | 96,82 | 134 | 44,45 | 114 | 28 | 21 | G1/4 - M12x1,5 | M20x100 | 3/4"x4" | 4225 | 2,03 |

**DESIGNAZIONE PER ORDINE
DESIGNATION FOR ORDER**

Distanziale con foro metrico
Distance piece with metric hole

Distanziale con foro gas
Distance piece with BSP hole

Materiale / Material

S355 **AISI 316L**

D...M.. **DX...M..**

D...G... **DX...G...**

NOTE / NOTES

* Solo in ST52.3

* Only in ST52.3